



Maku

Maku is a collection of porcelain stoneware tiles. It mimics matt stone in soft, natural colours that brings a touch of contemporary elegance to floors and walls. A fine-quality surface to strike a perfect balance between architectural rigour and essential warmth. Maku is the ideal covering material for outdoors, able to stand up to frost and wear. perfect as a covering material for stairs thanks to the special trims.

COLOUR



Maku Sand



Maku Nut



Maku Light



Maku Grey



Maku Dark

SIZE OPTIONS

	Dark	Grey	Nut	Sand	Light
750x750x10mm Matt	•	•	•	•	•
600x600x10mm Matt	•	•	•	•	•
600x300x10mm Matt	•	•	•	•	•
600x300x20mm Out	•	•	•	•	•

TECHNICAL DETAILS

Product: Maku is a full body porcelain stoneware tile. Unglazed, composed of a very fine mixture of quality clay with the addition of feldspar, quartz and kaolion. Manufactured by dry pressing of atomized powders and subsequently sintered by industrial firing at temperatures above 1200°C.

The complete vitrification of the tiles allows for a compact, non-absorbent, frost-proof product, resistant to bending, impacts, staining, chemical attacks and thermal shock.

Surface Finish: Matt and Out

Slip Resistance	Matt	Out
DIN 51130	R9	R11
DIN 51097	-	Group C
Pendulum 96 Rubber	-	-
Pendulum 55 Rubber	-	-

Manufacturing Standard: BS EN 14411G
(details available on request)

Use: All walls.
Dry internal floors – matt finish.
External and wet barefoot areas – out finish.

Variation: V2

Actual Size: Please note that these tiles have a sharp 90 degree edge for installation with a 2 or 3mm grout joint. The dimensions provided above are exact and therefore add the grout joint width to the overall module size when preparing setting out drawings.

Installation: Fit this range in a solid bed of polymer modified adhesive in accordance with BS5385: Parts 1, 2, 3 and 4. Adhesive and grout may vary in relation to the specific nature of the installation, and proposed substrates. Please enquire with our sales department for further information.

Grout Joint: Install these tiles with a minimum 3mm joint on floors and 2mm joint on walls.

Weight per square metre

600x600x10mm – 22.98 kg/m²

600x300x10mm – 21.38 kg/m²

750x750x10mm -23.06 kg/m²

600x300x20mm – 21.38 kg/m²