



Dreaming

Dreaming is a new interpretation of the most valued material in nature. The authentic appeal of rare and precious quarry stones, marble and onyx, creates a classic look with a modern feel. Various shaded tones and veining play with space, creating a disruptive dynamic effect. The lux finish allows light to highlight colours reflected from the tile. Whereas the velvet finish offers a new feel to a natural finish.

COLOUR



Dreaming Romance Safari



Dreaming Grey Stone



Dreaming Crystal White



Dreaming Calacatta Shine



Dreaming Bianco Statuario

SIZE OPTIONS

	10mm 595x296mm Lux / Velvet	10mm 595x595mm Lux / Velvet	10mm 1192x595mm Lux / Velvet	10mm 58x116cm Lux
Bianco Strutuario	•	•	•	•
Crystal White	•	•		
Romance Safari	•	•		
Calacatta Shine	•	•	•	•
Gray Stone	•	•	•	•

Lasa Aurora	•	•	•	•
Imperial Onyx	•	•	•	•

TECHNICAL DETAILS

Product: Dreaming is a coloured bodied porcelain stoneware tile, unglazed. Composed of a very fine mixture of quality clay with the addition of feldspar, quartz and kaolion. Manufactured by dry pressing of atomised powders and subsequently sintered by industrial firing at temperatures above 1200°C. The complete vitrification of the tiles allows for a compact, non-absorbent, frost-proof product, resistant to bending, impacts, staining, chemical attacks and thermal shock.

Surface Finish: lux and velvet.

Manufacturing Standard: Conforming to UNI EN 14411 ISO 13006 European Standards, Annex G (Group BLA UGL) (full details available on request)

Use: internal walls and floors

Variation: V3

Actual sizes: Please note that these tiles are supplied with sharp 90 degree edges for installation with a 2/3mm grout joint. The dimensions provided are exact and therefore the grout joint width should be added to select the overall module size when preparing setting out drawings.

Installation: We recommend that this range is bedded in a solid bed of polymer modified adhesive in accordance with BS5385: Parts 1, 2, 3 and 4. Adhesive and grouts required may vary in relation to the specific nature of the installation and proposed substrates. Please enquire with our sales department for further information.

Grout Joint: These tiles should be installed with a minimum 3mm joint on floors and 2mm joint on walls.

Weight per square metre:

10mm – 22.57kg/m²

11mm – 24.6kg/m²