



Nextone

Nextone is a collection of porcelain limestone tiles. The style of stone is a combination from four different quarries. Nextone also offers three contemporary textures: line, Dot and Mark. This collection is perfect for an easy flowing and coordinated environment. Such as: kitchens, bathrooms, open plan, office spaces or other commercial and residential areas. Looking for an outside stone? Nextone provide 20mm thick slabs in both Grip and Natural finishes. Furthermore, the textured styles in this range are great for creating a feature wall. Offering a modern yet unique design for your space.

COLOUR



Nextone White



Nextone Taupe



Nextone Grey



Nextone Dark

SIZE OPTIONS

	1192x595x10mm Natural	895x895x10mm Natural	895x445x10mm Natural	595x595x10mm Natural	595x595x10mm Grip	595x296x10mm Natural	1192x595x20mm Grip	595x595x20mm Grip
Dark	•	•	•	•	•	•	•	•
Grey	•	•	•	•	•	•	•	•
Taupe	•	•	•	•	•	•	•	•
White	•	•	•	•	•	•	•	•
Dot				•		•		
Line				•		•		
Mark				•		•		

TECHNICAL DETAILS

Product: Nextone is a full body porcelain stoneware tile. Unglazed, composed of a very fine mixture of quality clay with the addition of feldspar, quartz and kaolion. Manufactured by dry pressing of atomized powders and subsequently sintered by industrial firing at temperatures above 1200°C.

The complete vitrification of the tiles allows for a compact, non-absorbent, frost-proof product, resistant to bending, impacts, staining, chemical attacks and thermal shock.

Surface Finish: Natural and Grip.

Slip Resistance	Natural	Grip
DIN 51130	R10	R11
DIN 51097	Group B	Group C
Pendulum 96 Rubber	Wet: 38 Dry: 57	Wet: 45 Dry: 59
Pendulum 55 Rubber	- -	Wet: 37 Dry: 83

Variation: V4

Manufacturing Standard: BS EN 11411G (full details available on request)

Use: All internal/external walls – all finishes.

Dry internal floors – naturale finish

External and wet barefoot areas – grip finish.

Installation: We recommend a solid bed of polymer modified adhesive in accordance with BS5385: Parts 1, 2, 3 and 4.

Adhesive and grouts required may vary in relation to the specific nature of the installation, and proposed substrates.

Grout Joint: Install with a 2mm joint indoors and 5mm joint outdoors.

Weight per square metre

10mm – 22.57 kg/m²

20mm – 46.61 kg/m²